



Manhole Covers Ireland

We cover everything!

Portland, Lorrha, Nenagh, Co. Tipperary E45 DH99.

Phone 094 9033 022 Fax 094 92 54970

Email: info@mhcireland.com Website: www.mhcireland.com

T Range Hinged & Locked D400 C & F



Badged if Required

| Product Code | Overall Size | Clear Opening | Frame Height | 3 rd Party Certified |
|--------------|---------------|---------------|--------------|---------------------------------|
| MH-D-T60-60 | 800 x 730mm | 600 x 600mm | 100mm | Yes |
| MH-D-T60-120 | 775 x 1250mm | 600 x 1200mm | 125mm | Yes |
| MH-D-6767-10 | 750 x 750mm | 675 x 675mm | 100mm | Yes |
| MH-D-T76-120 | 1342 x 924mm | 1200 x 760mm | 100mm | Yes |
| MH-D-T80-70 | 1000 x 830mm | 800 x 700mm | 100mm | Yes |
| MH-D-T90-60 | 1030 x 800mm | 900 x 600mm | 100mm | Yes |
| MH-D-T90-90 | 1030 x 1100mm | 900 x 900mm | 100mm | Yes |
| MH-D-T106-70 | 1190 x 900mm | 1060 x 700mm | 100mm | Yes |
| MH-D-T150-75 | 1655 x 867mm | 1500 x 750mm | 100mm | Yes |
| MH-D-T90182 | 1951 x 1053mm | 1822 x 900mm | 110mm | Yes |
| MH-D-T75-214 | 2275 x 950mm | 2140 x 750mm | 100mm | Yes |

FRAME

It is realized in a single cast, the covers open in triangular section with double hinges, with the aim of having free access to 2/3 sides. Externally, the outside border is flanged to optimise its hold in the cement, and it has specific holes for the insertion of the anchoring bolts.

COVERS

It comes triangular; it is hinged to the frame with total opening of 110°. At 90° it assumes the automatic safety blocking position and can be removed without disassembling the hinge. This method allows partial and sequential opening with a coupling system placed on the edges, which reduces the infiltration of water. The master half cover section is provided with a stainless-steel lock, operable using a special shaped key which guarantees safety and prevents the opening of the manhole covers by Unauthorised personnel. Furthermore, the key becomes a comfortable handle for opening and closing the cover. The upper surface is designed to be non-skid to allow the complete flow of water and avoid the creation of ice.

INTENDED USE

It is designed for Road, footpaths and parking areas for all types of road vehicles (see norm EN 124-2 group 4). Manufactured to EN124-2 D400 and 3rd party certified (Copy available on Request)

TREATMENT

The manhole cover has a protective coating of black paint.